



Escalator Motor Line

Features:

- 3-Phase
- 380/400/415 Volt
- 50/60Hz
- 4 & 6 Pole
- Efficiency IE3
- 40°C Ambient
- Class F Insulation
- Continuous Duty Cycle
- TEFC
- Cast Iron Construction
- IEC Frame 132S-200L



No	Cat.No.	Model	KW	Pole	Voltage	Hz	Frame	Efficiency FL(%), 50Hz	Efficiency FL(%), 60Hz
1	BME-FT001	BTFT-132S-4	5.5	4	380/400/415	50/60	132S	89.6	91.7
2	BME-FT002	BTFT-132M-4	7.5	4	380/400/415	50/60	132S	90.4	91.7
4	BME-FT003	BTFT-160M-4	11	4	380/400/415	50/60	160M	91.4	92.4
6	BME-FT004	BTFT-160L-4	15	4	380/400/415	50/60	160L	92.1	92.4
7	BME-FT005	BTFT-180M-4	18.5	4	380/400/415	50/60	180M	92.6	93.6
8	BME-FT006	BTFT-180L-4	22	4	380/400/415	50/60	180L	93.0	93.6
9	BME-FT007	BTFT-132M-6	5.5	6	380/400/415	50/60	132M	88.0	91.0
10	BME-FT008	BTFT-160M-6	7.5	6	380/400/415	50/60	160M	89.1	91.0
11	BME-FT009	BTFT-160L-6	11	6	380/400/415	50/60	160L	90.3	91.7
12	BME-FT010	BTFT-180L-6	15	6	380/400/415	50/60	180L	91.2	91.7
13	BME-FT011	BTFT-200L-6	18.5	6	380/400/415	50/60	200L	91.7	93.0
14	BME-FT012	BTFT-200L-6	22	6	380/400/415	50/60	200L	92.2	93.0